

LGSISP01.8UL

ULTRA HIGH-RESOLUTION FINE PITCH
LED SCREENS FOR CONTROL ROOMS,
BROADCAST & PREMIUM SPACES



TECHNICAL SPECIFICATIONS

Ürün görseli buraya

- ☐ New generation full-flip chip microLED technology
- ☐ Adjustable brightness optionally up to 6.500 nits
- ☐ Production level calibration for best color uniformity
- ☐ Aluminum fanless design for high performance under extreme conditions
- ☐ Lightweight for easy adaptation and low cost framework design
- ☐ Lower power consumption with common-cathode technology

Yaşam tarzı / araba görseli buraya

LEDGARANTI ULTRA
FINE PITCH SOLUTIONS

- 1- Panel dimensions can change upon customer request
- 2- That value is the remain capacity of PSU's at 100% brightness and white color content
- 3- Different types of video input available as option

IDEAL FOR

Control Room Broadcast Studio Command Center Corporate Lobby Museum & Exhibition Premium Retail

ADVANCED FEATURES



GENERAL

Operating environment	:	indoor
Pixel pitch	:	1.87mm
Service type	:	front and rear access
Calibrated brightness (nits)	:	>700 nits
Lamp type	:	SMD
Lifespan (hours at %50 brightness)	:	>100.000 hours
White color calibration (adj.)	:	3.000K-8.500K
Gray scale	:	>16 bits
Brightness control	:	256 level

MODULE SPECIFICATIONS

Refresh frequency	:	3.840Hz
LED drive method	:	dynamic
Module material	:	aluminum
Module type	:	apparent
PCB type	:	multilayer
PCB surface coating	:	humiseal

PANEL SPECIFICATIONS

Panel material	:	aluminum
Panel dimensions (mm)	:	600x337.5
Diagonal size	:	27" [16:9]
Panel weight	:	<8 kg
Panel resolution	:	320x180px
Pixel density (pcs/sqm)	:	276.676
Viewing angle (horizontal x vertical)	:	>175° x 175°
Minimum viewing distance	:	>1.8m
Operating temperature range	:	0°C ~ +50°C
Storage temperature range	:	-20°C ~ +60°C
Operating humidity	:	10% ~ 90% non-condensing
Power input voltage	:	110 ~ 240 VAC
Power input frequency	:	50 ~ 60 Hz
Average power per sqm	:	<80W
Max power per sqm	:	<400W
Active PFC	:	YES
Load tolerance	:	25% min.
Panel installation type	:	Fixed installation
Cooling	:	Passive cooling

OTHER

Max input resolution	:	FHD, UHD, 4K, 8K
Standard video sources	:	All digital formats
Brightness adjustment	:	Automatic & manual
Death pixel monitoring	:	Optional
Module monitoring	:	YES
Temperature monitoring	:	YES
Smoke monitoring	:	Optional
Voltage monitoring	:	YES
Power redundancy	:	N/A
Signal path backup	:	YES
Signal transmission	:	CAT or Fiber Optic
Standby scheduling	:	YES
Power on/off scheduling	:	Optional
Power saving mode	:	YES
Certification	:	CE-EMC, CE-LVD, RoHS, FCC



LedGaranti reserves the right to change any product specification, discontinue of any product or services without prior notice. The icons above indicate optional features.

www.ledgaranti.com.tr