

LGAOSP12.5AR

HIGH-BRIGHTNESS LED SCREENS FOR
STADIUMS, ARENAS &
SPORTS VENUES



Ürün görseli buraya

- ☐ New generation full-flip chip microLED technology
- ☐ Adjustable brightness optionally up to 6.500 nits
- ☐ Production level calibration for best color uniformity
- ☐ Aluminum fanless design for high performance under extreme conditions
- ☐ Lightweight for easy adaptation and low cost framework design
- ☐ Lower power consumption with common-cathode technology

Yaşam tarzı / araba görseli buraya

LEDGARANTI STADIUM
LED SOLUTIONS

- 1- Panel dimensions can change upon customer request
- 2- That value is the remain capacity of PSU's at 100% brightness and white color content
- 3- Different types of video input available as option

IDEAL FOR

Stadium Arena & Sports Hall Scoreboard Perimeter Board Live Events Broadcast

ADVANCED FEATURES



TECHNICAL SPECIFICATIONS

GENERAL

Operating environment	:	outdoor
Pixel pitch	:	12.5mm
Service type	:	front and rear access
Calibrated brightness (nits)	:	>7.000 nits
Lamp type	:	SMD
Lifespan (hours at %50 brightness)	:	>100.000 hours
White color calibration (adj.)	:	3.500K-8.500K
Gray scale	:	>16 bits
Brightness control	:	256 level

MODULE SPECIFICATIONS

Module dimensions (mm)	:	400x300
Refresh frequency	:	adjustable
Module resolution	:	32x24
LED drive method	:	dynamic
Module material	:	aluminum
Module type	:	sealed
PCB type	:	multilayer
PCB surface coating	:	humiseal

PANEL SPECIFICATIONS

Panel material	:	aluminum
Panel paint	:	ES powder coated
Panel dimensions (mm)	:	1.600x900
IP level	:	IP67 front and rear
Panel weight	:	<40 kg
Panel resolution	:	128x72
Pixel density (pcs/sqm)	:	6.400
Viewing angle (horizontal x vertical)	:	>120° x 120°
Minimum viewing distance	:	>12m
Operating temperature range	:	-15°C ~ +50°C
Storage temperature range	:	-20°C ~ +60°C
Operating humidity	:	10% ~ 90% non-condensing
Power input voltage	:	110 ~ 240 VAC
Power input frequency	:	50 ~ 60 Hz
Average power per sqm	:	<120W
Max power per sqm	:	<600W
Active PFC	:	YES
Load tolerance	:	25% min.
Panel installation type	:	Fixed installation
Cooling	:	Passive cooling

OTHER

Max input resolution	:	FHD, UHD, 4K, 8K
Standard video sources	:	All digital formats
Brightness adjustment	:	Automatic & manual
Death pixel monitoring	:	Optional
Module monitoring	:	YES
Temperature monitoring	:	YES
Smoke monitoring	:	Optional
Voltage monitoring	:	YES
Power redundancy	:	N/A
Signal path backup	:	YES
Signal transmission	:	CAT or Fiber Optic
Standby scheduling	:	YES
Power on/off scheduling	:	Optional
Power saving mode	:	YES



LedGaranti reserves the right to change any product specification, discontinue of any product or services without prior notice. The icons above indicate optional features.

www.ledgaranti.com.tr