

LGCISP01.8FF

FLEXIBLE & CURVED LED SCREENS FOR
CREATIVE ARCHITECTURAL &
IMMERSIVE INSTALLATIONS



Ürün görseli buraya

- ☐ New generation full-flip chip microLED technology
- ☐ Adjustable brightness optionally up to 6.500 nits
- ☐ Production level calibration for best color uniformity
- ☐ Aluminum fanless design for high performance under extreme conditions
- ☐ Lightweight for easy adaptation and low cost framework design
- ☐ Lower power consumption with common-cathode technology

Yaşam tarzı / araba görseli buraya

LEDGARANTI FREEFORM
FLEXIBLE SOLUTIONS

- 1- Panel dimensions can change upon customer request
- 2- That value is the remain capacity of PSU's at 100% brightness and white color content
- 3- Different types of video input available as option

IDEAL FOR

Curved Surfaces Architecture & Facade Creative Retail Immersive Spaces Stage & Events Art & Exhibition

ADVANCED FEATURES

- Front Access
- Lightweight
- Slim
- Temp Monitoring
- Smoke Monitoring
- Voltage Monitoring
- Remote Control
- Easy To Install
- Wide Angle
- High Refresh Rate
- Transparent
- Noiseless
- Calibration
- Pixel Detection
- Fanless

TECHNICAL SPECIFICATIONS

GENERAL

Operating environment	:	indoor
Pixel pitch	:	1.8mm
Service type	:	front and rear access
Calibrated brightness (nits)	:	600 nits
Lamp type	:	SMD
Lifespan (hours at %50 brightness)	:	>100.000 hours
White color calibration (adj.)	:	3.500K-8.500K
Gray scale	:	>16 bits
Brightness control	:	256 level

MODULE SPECIFICATIONS

Module dimensions (mm)	:	320x160 / 240x120
Refresh frequency	:	3.840Hz
Module resolution	:	172x86px / 128x64px
LED drive method	:	dynamic
Module material	:	plastic (el.)
Module type	:	freeform
PCB type	:	multilayer thin film
PCB surface coating	:	tape film

PANEL SPECIFICATIONS

Panel material	:	steel
Panel paint	:	ES powder coated
Panel dimensions (mm)	:	adjustable
IP level	:	IP22 front and rear
Minimum curving diameter (mm)	:	300
Panel resolution	:	adjustable
Pixel density (pcs/sqm)	:	284.444
Viewing angle (horizontal x vertical)	:	>120° x 120°
Minimum viewing distance	:	>1.8m
Operating temperature range	:	0°C ~ +50°C
Storage temperature range	:	-20°C ~ +60°C
Operating humidity	:	10% ~ 90% non-condensing
Power input voltage	:	110 ~ 240 VAC
Power input frequency	:	50 ~ 60 Hz
Average power per sqm	:	<120W
Max power per sqm	:	<600W
Active PFC	:	YES
Load tolerance	:	25% min.
Panel installation type	:	Fixed installation
Cooling	:	Passive cooling

OTHER

Max input resolution	:	FHD, UHD, 4K, 8K
Standard video sources	:	All digital formats
Brightness adjustment	:	Automatic & manual
Death pixel monitoring	:	Optional
Module monitoring	:	YES
Temperature monitoring	:	YES
Smoke monitoring	:	Optional
Voltage monitoring	:	YES
Power redundancy	:	N/A
Signal path backup	:	YES
Signal transmission	:	CAT or Fiber Optic
Standby scheduling	:	YES
Power on/off scheduling	:	Optional
Power saving mode	:	YES
Certification	:	CE-EMC, CE-LVD, RoHS, FCC



LedGaranti reserves the right to change any product specification, discontinue of any product or services without prior notice. The icons above indicate optional features.

www.ledgaranti.com.tr