

# LGAISP01.9STQ

HIGH-REFRESH RENTAL LED SCREENS FOR  
CONCERTS, EVENTS &  
BROADCAST STAGES



Ürün görseli buraya

- ☐ New generation full-flip chip microLED technology
- ☐ Adjustable brightness optionally up to 6.500 nits
- ☐ Production level calibration for best color uniformity
- ☐ Aluminum fanless design for high performance under extreme conditions
- ☐ Lightweight for easy adaptation and low cost framework design
- ☐ Lower power consumption with common-cathode technology

Yaşam tarzı / araba görseli buraya

LEDGARANTI STAGE  
RENTAL SOLUTIONS

- 1- Panel dimensions can change upon customer request
- 2- That value is the remain capacity of PSU's at 100% brightness and white color content
- 3- Different types of video input available as option

## IDEAL FOR

Concert & Live Show Events & Festivals Broadcast Studio Theater & Stage Corporate Events Touring & Rental

## ADVANCED FEATURES

- Front Access
- Lightweight
- Slim
- Temp Monitoring
- Smoke Monitoring
- Voltage Monitoring
- Remote Control
- Easy To Install
- Wide Angle
- High Refresh Rate
- Transparent
- Noiseless
- Calibration
- Pixel Detection
- Fanless

## TECHNICAL SPECIFICATIONS

### GENERAL

|                                    |   |                       |
|------------------------------------|---|-----------------------|
| Operating environment              | : | indoor                |
| Pixel pitch                        | : | 1.9mm                 |
| Service type                       | : | front and rear access |
| Calibrated brightness (nits)       | : | 800~1.000 nits        |
| Lamp type                          | : | 4in1 MiniLED          |
| Lifespan (hours at %50 brightness) | : | >100.000 hours        |
| White color calibration (adj.)     | : | 3.500K~8.500K         |
| Gray scale                         | : | >16 bits              |
| Brightness control                 | : | 256 level             |

### MODULE SPECIFICATIONS

|                        |   |              |
|------------------------|---|--------------|
| Module dimensions (mm) | : | 250x250      |
| Refresh frequency      | : | 3.840Hz      |
| Module resolution      | : | 128x128px    |
| LED drive method       | : | dynamic      |
| Module material        | : | plastic (PC) |
| Module type            | : | sealed       |
| PCB type               | : | multilayer   |
| PCB surface coating    | : | humiseal     |

### PANEL SPECIFICATIONS

|                                       |   |                          |
|---------------------------------------|---|--------------------------|
| Panel material                        | : | die-casting aluminum     |
| Panel paint                           | : | ES powder coated         |
| Panel dimensions (mm)                 | : | 500x500                  |
| IP level                              | : | IP22 front and rear      |
| Panel weight                          | : | <8 kg                    |
| Panel resolution                      | : | 256x256px                |
| Pixel density (pcs/sqm)               | : | 262.144                  |
| Viewing angle (horizontal x vertical) | : | >120° x 120°             |
| Minimum viewing distance              | : | >2m                      |
| Operating temperature range           | : | 0°C ~ +50°C              |
| Storage temperature range             | : | -20°C ~ +60°C            |
| Operating humidity                    | : | 10% ~ 90% non-condensing |
| Power input voltage                   | : | 110 ~ 240 VAC            |
| Power input frequency                 | : | 50 ~ 60 Hz               |
| Average power per sqm                 | : | <120W                    |
| Max power per sqm                     | : | <600W                    |
| Active PFC                            | : | YES                      |
| Load tolerance                        | : | 25% min.                 |
| Panel installation type               | : | Rental type              |
| Cooling                               | : | Passive cooling          |

### OTHER

|                         |   |                           |
|-------------------------|---|---------------------------|
| Max input resolution    | : | FHD, UHD, 4K, 8K          |
| Standard video sources  | : | All digital formats       |
| Brightness adjustment   | : | Automatic & manual        |
| Death pixel monitoring  | : | Optional                  |
| Module monitoring       | : | YES                       |
| Temperature monitoring  | : | YES                       |
| Smoke monitoring        | : | Optional                  |
| Voltage monitoring      | : | YES                       |
| Power redundancy        | : | N/A                       |
| Signal path backup      | : | YES                       |
| Signal transmission     | : | CAT or Fiber Optic        |
| Standby scheduling      | : | YES                       |
| Power on/off scheduling | : | Optional                  |
| Power saving mode       | : | YES                       |
| Certification           | : | CE-EMC, CE-LVD, RoHS, FCC |



LedGaranti reserves the right to change any product specification, discontinue of any product or services without prior notice. The icons above indicate optional features.

www.ledgaranti.com.tr