

P1.875 Indoor Rental LED

INDOOR
İÇ MEKAN

TECHNICAL SPECIFICATIONS

LED Lamp	
Type	SMD1515
Brand	MLS / Nationstar Lamp
Arrangement	1R1G1B
Chip parameters	Red(620-625nm) IV:(250-300mcd)
Chip parameters	Green(520-525nm) IV:(450-550mcd)
Chip parameters	Blue(470-475nm) IV:(100-120mcd)
LED Module	
Pixel Pitch	1.875mm
Module Size	240x240mm
Module Resolution	128x128=16384(Dots)
Module Weight	0.8kg
LED Cabinet	
Pixel Density	284444 Dots/sqm
Frame Frequency	no less than 60 frame/sec
Cabinet Resolution	256x256=65536(Dots)
Input Voltage	AC110-220V±10%, 50/60Hz
Cabinet Dimension(W*H*D)	480x480x65mm
Output Voltage	DC-4.5V, 40A
Module Quantity /Cabinet	2x2=4(Pcs)
Color Grayscale	16bit
Gray Scale per Color	65536 level
Cabinets Material	Nanomaterial
Color Processing	R(1024)xG(1024)xB(1024)
Cabinet Weight	4.8kg
Brightness Adjustment	256 color levels, can be adjusted manually and automatically optional
Brightness	1000cd/sqm
MTBF(mean time between failures)	10000 hours
Viewing Angle	120(Horizontal), 120(Vertical)
Life-span	100, 000 hours
Nearest Viewing Distance	2m
Protection Level(front/back)	IP54
Power Consumption (Max)	800 w/sqm
Power Consumption (Average)	260 w/sqm
Malfunction Dot Rate	less than 0.0001
Working Temperature	-10°C-60°C
Display Function	Text, Graphics, Video
Humidity	10%-90%
Refresh Rate	>3840Hz
Drive Mode/Driver Position	Constant driving 1/32 Scan, Combined driver board
Control System	
Control Mode	Synchronization/Asynchronization
Input Signal	AVI/MPG/MPEG/TXT.etc
Control System	Sending Card, Receiving Card, Receiving HUB
PC Operating System	Microsoft Windows 10 ,Windows 7 and XP
Software	LED Studio(HSTV-linsn)
Communication Type	Net cable; 3G, WIFI(Sold separately)
Language	Chinese, Traditional Chinese, English, French, Japanese, Russian, Thai, Spanish, Polish, Italian, Portuguese, Turkish, Dutch, Greek, Bulgarian, Romanian, Arabic,Korean,German
Certificate	CE, ROHS, FCC, ISO9001, TUV
Control Card Input	DVI, USB; RJ45, HDMI(Sold separately)



Resimlerinizde Her Detayı Sağlayın

- Gri Ölçek - Daha Güzel Fotoğraflar
- Yüksek Çözünürlük
- Dikkatlice Ürün Yüklemesi
- Hepsi için Tek Fiyat



Su geçirmez
kauçuk conta



Modüller arası sinyal
ve elektrik bağlantısı



Patentli Mask Tasarımı



UV ışınlarına ve deformasyona
dayanıklı modül kit



En üst seviye
koruyucu kaplama



Modül içi
sinyal bağlantısı