

Cephe Serisi

OUTDOOR FINE PITCH LED SCREENS FOR
DIGITAL OUT-OF-HOME MESSAGING &
PROFESSIONAL INSTALLATIONS



Ürün görseli buraya

- ☐ New generation full-flip chip microLED technology
- ☐ Adjustable brightness optionally up to 6.500 nits
- ☐ Production level calibration for best color uniformity
- ☐ Aluminum fanless design for high performance under extreme conditions
- ☐ Lightweight for easy adaptation and low cost framework design
- ☐ Lower power consumption with common-cathode technology

Yaşam tarzı / araba görseli buraya

LEDGARANTI OUTDOOR
FINE PITCH SOLUTIONS

- 1- Panel dimensions can change upon customer request
- 2- That value is the remain capacity of PSU's at 100% brightness and white color content
- 3- Different types of video input available as option

IDEAL FOR

DOOH Advertising Shopping Malls Stadiums Corporate Buildings Transport Hubs Control Rooms

ADVANCED FEATURES



TECHNICAL SPECIFICATIONS

GENERAL

Chipset	:	
Operating environment	:	outdoor
Pixel pitch	:	1.53mm
Service type	:	front and rear access
Calibrated brightness (nits)	:	3.800 nits
Lamp type	:	Flip-Chip Micro
Lifespan (hours at %50 brightness)	:	>80.000 hours
White color calibration (adj.)	:	3.500K-8.500K
Gray scale	:	>24bits
Brightness control	:	256 level

MODULE SPECIFICATIONS

Module dimensions (mm)	:	160x360
Refresh frequency	:	3.840Hz
Module resolution	:	104x232px
LED drive method	:	dynamic
Module material	:	aluminum
Module type	:	sealed
PCB type	:	multilayer
Surface coating	:	UV resistant & high contrast

PANEL SPECIFICATIONS

Panel material	:	aluminum
Panel paint	:	ES powder coated
Panel dimensions (mm)	:	640x360
Panel depth	:	70mm
IP level	:	IP65 rear
Panel weight	:	8.5kg
Panel resolution	:	416x232px
Pixel density (pcs/sqm)	:	418.888
Viewing angle (horizontal x vertical)	:	175° x 160°
Minimum viewing distance	:	>1.5m
Operating temperature range	:	-20°C ~ +40°C
Storage temperature range	:	-30°C ~ +60°C
Operating humidity	:	10% ~ 80% non-condensing
Power input voltage	:	100 ~ 240 VAC
Power input frequency	:	50-60Hz
Average power per sqm	:	<200W
Max power per sqm	:	<600W
Active PFC	:	YES
Load tolerance	:	25% min.
Panel installation type	:	Fixed installation
Cooling	:	Passive cooling without fan

OTHER

Max input resolution	:	FHD, UHD, 4K, 8K
Standard video sources	:	All digital formats
Brightness adjustment	:	Automatic & manual
Death pixel monitoring	:	Optional
Module monitoring	:	YES
Temperature monitoring	:	YES
Smoke monitoring	:	Optional
Voltage monitoring	:	YES
Power redundancy	:	N/A
Signal path backup	:	YES
Signal transmission	:	CAT or Fiber Optic
Standby scheduling	:	YES
Power on/off scheduling	:	Optional
Power saving mode	:	YES
Certification	:	CE-EMC, CE-LVD, RoHS, FCC

OPTIONS

Contrast ratio	:	10.000:1
Higher Brightness - CLX	:	6.500 nits
Corner installation	:	N/A



LedGaranti reserves the right to change any product specification, discontinue of any product or services without prior notice. The icons above indicate optional features.

www.ledgaranti.com.tr